

Mini-HDMI™ adapter cable with Ethernet

high speed adapter from HDMI™ to Mini-HDMI™

Enjoy movies and games clearly in high resolution and dazzling quality. What does this cable do to an audio video signal? Nothing. It is, however, precisely this feature which proves its quality. Thanks to pure materials, precise processing, and modern technology, it combines your HDMI™ device with mobile appliances. Therefore, you can be sure that you get the experience exactly as it was meant to be.

- suitable for digital connection of mobile devices
- pure copper conductor and 2-way shielding for clear signal quality
- High Speed HDMI™ for 3D and HDTV up to 4K (2160p)
- integrated Ethernet channel saves additional network or audio cables
- 24-Karat gold plated contacts for minimum transfer resistances

Specifications

Connections	
Plug material:	triple-coated PVC / ABS
Contact material:	24-Karat gold plated
Shielding:	yes
Port 1, type:	HDMI™ connector (type A)
Connector 1, connector length (mm):	42.1
Connector 1, connector width (mm):	20.4
Connector 1, connector height (mm):	11.4
Port 2, type:	HDMI™ mini connector (type C)
Connector 2, connector length (mm):	36.3
Connector 2, connector width (mm):	14.0
Connector 2, connector height (mm):	8.4

cable	
Type:	Round cable
Length (m):	1 2 3 5
Inner conductor material:	OFC (Oxygen free copper)
Inner conductor diameter (mm):	1 x 0.250
AWG:	30
Number of shieldings:	2 x
Type of 1st shielding	Aluminium foil
Type of 2nd shielding	Copper braid 112 wires x 0.10 mm cross section
Outer sheath material:	highly elastic PVC
Outer sheath diameter (mm):	6.0
Kink protection:	on both sides

Signal transmission	
Transmission modes:	digital audio and video signals
max. Bandwidth (MHz):	340
max. Transfer rate (Gb / s)	10.2
max. Resolution:	4K (2160p)
Supported color spaces:	16/24 bit RGB/YUV, Deep Color, x.v.Color™
Supported audio standards:	Audio-Return Channel (ARC), Dolby Digital/Plus, Dolby TrueHD, DTS-HD Master Audio™, DVD-Audio, SA-CD
Other supported standards:	HDMI™ Ethernet Channel (HEC), 3D, HDCP, CEC, 4K (2160i/p), Full HD (1080i/p), HD ready (720i/p), SDTV (480i/p)
Characteristic impedance (Ω):	100


General	
Operating temperature from / to (°C):	-10 / +80
Certification:	(ATC) Authorized Testing Centers
Warranty (years):	10

clicktronic®
entertainment.
pure.


casual



HDMI™ connector (type A) HDMI™ mini connector (type C)



Cross section



Wiring diagram

Type C PIN	Signal Assignment		Type A PIN
2 Blue			Blue 1
1 Earth			Earth 2
3 White			White 3
5 Blue			Blue 4
4 Earth			Earth 5
6 White			White 6
8 Blue			Blue 7
7 Earth			Earth 8
9 White			White 9
11 Blue			Blue 10
10 Earth			Earth 11
12 White			White 12
13	Green	DDC/CEC Ground	Green 17
14	White	CEC	White 13
15	Orange	SCL	Orange 15
16	Purple	SDA	Purple 16
17	Gray		Gray 14
18	Red	+5 Volts Power	Red 18
19	Yellow	Hot Plug Detect	Yellow 19