

Data sheet

GSN 20 schwarz/black - GSN 20 schwarz/black

Industrial Connectors:Rectangular connectors GDM-series:Type B EN 175301-803 (DIN 43650) / ISO 6952:Appliance connector:GSN 20 schwarz/black

Name GSN 20 schwarz/black



Delivery informations

Document created at 27-06-2010

Availability available

Product description

Description appliance connector with, central screws (hollow), 1 screw M 3 x 4

Type GSN 20 schwarz/black

Order No. 932 421-100

Number of contacts 2 + PE

Standard DIN EN 175 301-803-B

Housing Color black

Construction type B

Technical data

Rated voltage AC/DC 250 V

Rated current 16 A

Contact resistance <= 4 mOhm

Type of termination solder (ground contacts: screw)

Mounting screw

Material

Contact surface material Sn

Contact bearer material PA

Housing material PA

Environmental conditions

Protection class (IEC 60529) IP 65 (in plugged condition)

Pollution severity 3

Temperature range -40 °C to +125 °C

Inflammability class

Housing 94 V-1

Contact bearer 94 HB

Approvals

UR UR

VDE VDE

SEV SEV

Packing unit

Packaging unit 50 pieces

Scope of delivery and accessories

Accessories to order separately (NBR) flat gasket GSN 20-3, Order No. 733 275-002; (EPDM) flat gasket GSN 20-6, Order No. 733 270-004

Industrial Connectors:Rectangular connectors GDM-series:Type B EN 175301-803 (DIN 43650) / ISO 6952:Appliance connector:GSN 20 schwarz/black

Picture

Drawing

