

MINI MCR-SL-I-U-4

Tilausnumero: 2813538

Illustration shows the product MINI MCR-SL-U-I-O



<http://eshop.phoenixcontact.fi/phoenix/treeViewClick.do?UID=2813538>

MCR 3-way isolating amplifier, for electrical isolation of analog signals, with screw connection, input signal: 4 mA ... 20 mA, output signal: 0 A ... 10 V



Kaupalliset tiedot	
Nettohinta	92,0250 EUR / 1
EAN	
Pakkaus	1 kpl.
Tullitariffi	85437090
Gross weight in pieces	0,0714 kg
Tuoteluettelossa	Sivu 357 (IF-2011)

Tuotekohtaiset lisätiedot

WEEE/RoHS-yhteensopiva seuraavasta päivästä lähtien: 11.04.2006



Huomioithan, että tiedot on otettu online-luettelosta. Täydelliset tekniset tiedot voit ladata osoitteesta <http://www.download.phoenixcontact.com>. Yleiset toimitus- ja käyttöehdot koskevat myös Internet-latauksia.

Tekniset tiedot

Input data	
Configurable/programmable	No
Current input signal	4 mA ... 20 mA
Max. input current	50 mA
Input resistance current input	Approx. 50 Ω

Output data

Configurable/programmable	No
Voltage output signal	0 V ... 10 V
Max. output voltage	12.5 V
Short-circuit current	Approx. 2 mA
Load/output load voltage output	$\geq 10 \text{ k}\Omega$

Power supply

Nominal supply voltage	24 V DC
Supply voltage range	19.2 V DC ... 30 V DC (to bridge the supply voltage, the DIN rail connector (ME 6,2 TBUS-2 1,5/5-ST-3,81 GN, Order No. 2869728) can be used. It can be snapped onto a 35 mm DIN rail according to EN 60715)
Max. current consumption	< 9 mA
Power consumption	< 200 mW

Connection data

Connection method	Screw connection
Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	2.5 mm ²
Conductor cross section stranded min.	0.2 mm ²
Conductor cross section stranded max.	2.5 mm ²
Conductor cross section AWG/kcmil min.	26
Conductor cross section AWG/kcmil max	12
Stripping length	12 mm
Screw thread	M3

General data

Width	6.2 mm
Height	93.1 mm
Depth	102.5 mm
Maximum transmission error	$\leq 0.1 \%$ (of final value)
Maximum temperature coefficient	< 0.01 %/K
Temperature coefficient, typical	< 0.002 %/K
Limit frequency (3 dB)	Approx. 100 Hz
Step response (10-90%)	Approx. 3.5 ms
Ambient temperature (operation)	-20 °C ... 65 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C

Degree of protection	IP20
Electrical isolation	Basic insulation according to EN 61010
Surge voltage category	II
Pollution degree	2
Rated insulation voltage	50 V AC/DC
Test voltage, input/output/supply	1.5 kV (50 Hz, 1 min.)
Electromagnetic compatibility	Conformance with EMC Directive 2004/108/EC
Noise emission	EN 61000-6-4
Color	green
Housing material	PBT
Mounting position	Any
Assembly instructions	The DIN rail bus connector (TBUS) can be used for bridging the supply voltage. It can be snapped onto a 35 mm EN 60715 DIN rail.
Conformance	CE-compliant
ATEX	Ex II 3 G Ex nA IIC T4 Gc X
UL, USA / Canada	UL 508 Recognized
	Class I, Div. 2, Groups A, B, C, D T5 applied for
GL	GL EMC 2 D

Sertifikaatit

Certification	CUL, GL, UL
---------------	-------------


Lisätarvikkeet

Tuote	Merkintä	Kuvaus
General		
2869728	ME 6,2 TBUS-2 1,5/5-ST-3,81 GN	DIN rail connector (TBUS), 5-pos., for bridging the supply voltage, can be snapped onto NS 35/... DIN rails according to EN 60715
2308111	MINI MCR DKL	Fold up transparent cover for MINI MCR modules with additional labeling option using insert strips and flat Zack marker strip 6.2 mm
2810272	MINI MCR-DKL-LABEL	Label for extended marking of MINI MCR modules in connection with the MINI MCR-DKL
2864134	MINI MCR-SL-PTB	MCR power terminal block for supplying several MINI Analog modules via the DIN rail connectors, with screw connection, current consumption up to max. 2 A


2864147	MINI MCR-SL-PTB-SP	MCR power terminal block for supplying several MINI-ANALOG modules via the DIN rail connectors, with spring-cage connection, current consumption up to max. 2 A
2811268	MINI MCR-SL-V8-FLK 16-A	Eight MINI analog signal converters with screw connection method can be connected to a control system using a system adapter and system cabling with a minimum of wiring and very low error risk.
2866653	MINI-PS-100-240AC/24DC/1.5/EX	DIN rail power supply unit, primary-switched mode, slim design, output: 24 V DC / 1.5 A, ATEX approval
2866983	MINI-SYS-PS-100-240AC/24DC/1.5	DIN rail power supply unit, primary-switched mode, slim design, output: 24 V DC / 1.5 A

Piirrokset


Block diagram



Dimensioned drawing



Circuit diagram



Connection data incl. use groups



Osoite

Phoenix-Contact Oy
Niittytie 11
01300 Vantaa, Finland
Puhelin +358 (0)9-350 9020
Faksi +358 (0)9-351 3400
<http://www.phoenixcontact.fi>



Phoenix Contact Oy
Tekniset modifikaatiot mahdollisia;