

# ROCKER SWITCHES

PRODUCT NUMBER 1939.3119



## TECHNICAL DATA

|                                       |                                                                       |         |
|---------------------------------------|-----------------------------------------------------------------------|---------|
| Product number                        | 1939.3119                                                             |         |
| Business unit                         | Switches, Sensors & Controls                                          |         |
| Product Manager                       | Heinichen                                                             |         |
| Product family                        | Rocker switches                                                       |         |
| Actuation type                        | direct                                                                |         |
| Packing unit                          | 100                                                                   |         |
| Weight                                | 13.650 g                                                              |         |
| ROHS conform                          | yes                                                                   |         |
| Output                                | catalog before 2009 / catalog                                         |         |
| Distributor                           | REPRO                                                                 |         |
| Switching function                    | Changeover switch with OFF position in the center (DPDT - Center OFF) |         |
| Material fixed contact                | Ag                                                                    |         |
| Number of poles                       | 2 - pole                                                              |         |
| connections                           | Quick-connect terminal, 6.3 x 0.8                                     |         |
| Rating IEC                            | 12 (4) A 250 V AC 1E4                                                 |         |
| Rating North America                  | 14 A 250 V AC 3/4 HP<br>14 A 125 V AC 1/3 HP                          |         |
| Contact resistance (new condition)    | < 100 (1 A 12 V DC) mOhm                                              |         |
| Insulation resistance (new condition) | > 100 (500 V DC) MOhm                                                 |         |
| Voltage strength at 250 V             | → function insulation / basic insulation                              | 1 500 V |
|                                       | → reinforced insulation                                               | 3 000 V |
|                                       | → small contact distance                                              | 500 V   |
| Proof tracking                        | 250 PTI                                                               |         |
| Insulation spacing                    | acc. to EN 61058 for reinforced or double insulation                  |         |
| Protection type                       | → Connection                                                          | IP 40   |
|                                       | → Actuator                                                            | IP 65   |
| Ambient temperature                   | -30 °C ... +105 °C                                                    |         |
| Ambient temperature                   | -30 °C ... +55 °C                                                     |         |
| Storage temperature                   | -40 °C ... +80 °C                                                     |         |
| Flammability                          | UL 94 V-2                                                             |         |

|                                             |                                                                               |
|---------------------------------------------|-------------------------------------------------------------------------------|
| Glow wire test temperature                  | 850 °C                                                                        |
| Actuators and additional actuators          | hard component: PC, black, identification white<br>soft component: TPU, black |
| Housing description                         | housing: PA, black<br>base plate: PA, black                                   |
| Connection surface                          | → bearing connection silver plated<br>→ external connection silver plated     |
| Contact material                            | Ag                                                                            |
| Contact distance                            | ≥ 3 mm                                                                        |
| Rating Code UL                              | R 193                                                                         |
| Contact type                                | lifting contact                                                               |
| Plug force of the terminals                 | ≤ 80 N                                                                        |
| Approval marks                              | cCSAus / ENEC 05                                                              |
| Suitable for appliances of protection class | II                                                                            |
| Additional labeling                         | year/week of manuf. acc. to DIN EN 60062                                      |
| Type of fastening                           | Snap fastening                                                                |
| Degree of pollution                         | 3                                                                             |
| Stock version                               | ●                                                                             |

Technical changes reserved. Dimensions are not binding.

Detailed specifications available on request.

---

Marquardt GmbH · Schloss-Straße 16 · 78604 Rietheim-Weilheim · Germany  
Phone: +49 (0) 7424 / 99-0 · Fax: +49 (0) 7424 / 99-2399 · [www.marquardt.com](http://www.marquardt.com) · [marquardt@marquardt.de](mailto:marquardt@marquardt.de)