

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT copyright.d8Ye-

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A2	ECR-16-010931 UPDATE NAME	02AUG2016	L.Z	X.X

18.0HEX

13.5

22.00

18.0

11

PG9

M12

1

2

4

3

6

"L"±0.05M

PIN 1-BROWN

PIN 2-WHITE

PIN 5-GRAY

PIN 3-BLUE

PIN 4-BLACK

POTTING

5

TABLE 1

TECHNICAL DATA	T4171010002-00L	T4171010003-00L	T4171010004-00L	T4171010005-00L
RATED VOLTAGE	250V	250V	250V	60V
RATED CURRENT	4A	4A	4A	4A
POLLITION DEGREE	3	3	3	3
OVERVOLTAGE CATEGORY	II	II	II	II
MATERIAL GROUP	II	II	II	II
CONTACT RESISTANCE	<=10mΩ	<=10mΩ	<=10mΩ	<=10mΩ
INSULATION RESISTANCE	>100MΩ	>100MΩ	>100MΩ	>100MΩ
DEGREE OF PROTECTION	IP67	IP67	IP67	IP67
OPERATION TEMPEATURE	-40~85°C	-40~85°C	-40~85°C	-40~85°C

NOTE:

1. TECHNICAL DATA: SEE TABLE 1

2. PRODUCT COMPLIES WITH IEC61076-2-101

3. PLASTIC INERT MATERIAL:UL LISTED WITH UL94V0 FLAME RATING

4. CABLE LENGTH SEE TABLE 2

注释:

1:技术参数,见表1

2:产品符合标准IEC61076-2-101

3:塑胶材料符合UL标准,UL-94V0阻燃等级

4:线长度见表2

WIRE P N AND COLOR:	CABLE LENGTH	DESCRIPTION	POS	TABLE 2 P N
1(BR)/2(WH)/3(BL)/4(BK)/5(GR)	-001:0.2M -002:0.5M -003:1.0M -004:1.5M -005:3.0M -006:5.0M -007:7.0M -008:10.0M	RPC-M12-MF-5CON-PG9-**LAU	5	T4171010005-00L
		RPC-M12-MF-4CON-PG9-**LAU	4	T4171010004-00L
		RPC-M12-MF-3CON-PG9-**LAU	3	T4171010003-00L
		RPC-M12-MF-2CON-PG9-**LAU	2	T4171010002-00L

CABLE CHARACTERISTIC	CABLE LENGTH "L"	DESCRIPTION	POS	TABLE 2 P N
FLASH GOLD	COPPER ALLOY	CABLE	6	2 3 4 5
-	COPPER ALLOY	CONTACT	5	2 3 4 5
-	-	METAL NUT	4	1 1 1 1
-	-	O-RING	3	1 1 1 1
-	COPPER ALLOY	M12,MALE,METAL BODY	2	1 1 1 1
BLACK	NYLON	M12,MALE HSG, A CODE, 5PINS	1	1 1 1 1
COMMENT	MATERIAL	DESCRIPTION	ITEM	T4171010002-00L T4171010003-00L T4171010004-00L T4171010005-00L

Ch1x45°

Ch1x45°

Ch1x45°

RECOMMENDED PANEL CUTOUT

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN BO GAO 29MAR2016

CHK KOBBY ZHAO 29MAR2016

APVD XIANG XU 29MAR2016

DIMENSIONS: mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ±0.2

1 PLC ±0.2

2 PLC ±0.2

3 PLC ±0.2

4 PLC ±0.2

ANGLES ±

FINISH

PRODUCT SPEC 108-106140

APPLICATION SPEC 114-137144

WEIGHT

CUSTOMER DRAWING

NAME M12 PANEL MOUNT CONNECTOR A CODE, MALE, REAR MOUNTING

SIZE A2

CAGE CODE

DRAWING NO C-T417101000X00L

RESTRICTED TO

SCALE 2:1

SHEET 1 OF 1

REV A2

TE Connectivity

1471-9 (3/13)