



MILAN S.r.l. a socio unico

Head Office – Export department:

Viale Europa, 74
20090 Cusago (MI) Italy
T. +39 02 9039.4556-4158
F. +39 02 9039.4551
www.taskercables.com

Ufficio Commerciale e Centro Distribuzione

Viale Europa 72 Strada F12
20090 Cusago (MI) Italy
T. +39 02 9039.0037-0059
F. +39 02 9039.0049
www.tasker.it

Technical Datasheet

tasker® C200 – 2x0,08 mm²

Special Audio/Video Cable



CATEGORY Special Audio/Video Cable (See Audio Catalogue)
APPLICATIONS S-VHS and Mini DIN4 connectors.

- A:** Black Soft **PVC** Sheath. Outer cable Diam. Ø 4,60 (±0,10) mm.
- B:** Insulation with PVC, colored one Red and one White.
Diam. Ø: 2,00 (±0,10) mm.
- C:** Each conductor is Shielded with O.F.C. tinned copper spiral covering 100%.
- D:** O.F.C. tinned copper formation 12x0,10 mm.
Nom. Cross section 2x0,08 mm².

MARKING tasker® C200 2x0,08 mm² O.F.C. S-VHS Video Cable
CUSTOM PRODUCTION This product may be custom produced also in L.S.Z.H. polymer, PE, PUR, or Metallic Armored.

Cable Properties

Conductor Resistance	203 Ω/Km
Capacity Core/Core	65 pF/mt
Capacity Core/Shield	230 pF/mt
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			