



Type:	57671	Systems to charge:	Ni-MH
Designation:.....	LCD Multi Charger	Cell sizes:.....	AAA, AA
		Cell Configurations:.....	AAA, AA 2 / 4 / 6 / 8 pcs.

Dimensions:	Charger:	AC/DC-Adapter:
-------------	----------	----------------

Length:.....	167 ± 1 mm	76.4 ± 1 mm
Width:.....	106 ± 1 mm	43.2 ± 1 mm
Height:.....	32 ± 1 mm	30 ± 1 mm
Weight:.....	198 ± 1 g	111 ± 1 g

Charging methods:	AC adaptor input(200-240V 50Hz) 5.4V 3A:
-------------------	--

AA:.....	Current: 450mA ± 10%
AAA:.....	Current: 200 mA ± 10%
5V USB:.....	Current:1000 mA ± 10%

Housing:

Housing Material:.....	PA765
Casing color:.....	Black

Indications: LCD display

AAA, AA,cell mix:.....	1st bar flashing <1.39V
AAA, AA,cell mix:.....	1st bar solid and 2nd bar flashing <1.41V
AAA ,AA,cell mix:.....	1st and 2nd bars solid and 3th bar flashing <1.45V
AAA ,AA,cell mix:.....	1st, 2nd and 3th bars solid and 4th bar flashing <1.54V
AAA ,AA,cell mix:.....	All bars are solid : -dv

Protective Functions:

Reverse protection	Mechanical arrangement
Short circuit protection	No current, LCD flash

Power:

Primary:.....	200-240V AC 50 Hz
Secondary:.....	2.8V

Cut off criteria:

Ni-MH standard cells:...	Timer: 6.5 hours + / - 1 hour for AA/AAA
	-DV: 10mV +/- 2mV / Channel, function immediately
	Vmax: >1.65V

No publication or circulation of data to third parties without consent of VARTA Consumer Batteries