




DIN 911

~ISO 2936

Standard withdrawn

**BN 1169****Hex socket keys****A:** metric; **B:** UNC/UNF

Steel heat-treated

black

- ~UNI 6753

Article#	s	Tolerance	L ₁	L ₂	type
1380869	0,7	0,011 / -0,002	32	6	A
1380931	0,9	-0,011 / -0,024	32	10	A
1380478	1,3	-0,030 / -0,056	40	12	A
1380605	1,5	0 / -0,025	45	14	A
1380613	2	0 / -0,04	50	16	A
1411047	2,5	0 / -0,04	56	18	A
1411055	3	0 / -0,04	63	20	A
1411063	4	0 / -0,048	70	25	A
1411071	5	0 / -0,048	80	28	A
1411098	6	0 / -0,048	90	32	A
1411101	7	0 / -0,058	95	34	A
1411128	8	0 / -0,058	100	36	A
1411136	9	0 / -0,058	112	40	A
1411144	10	0 / -0,058	112	40	A
1411152	12	0 / -0,110	125	45	A
1411160	14	0 / -0,11	140	56	A
1411179	17	0 / -0,11	160	63	A
1411187	19	0 / -0,13	180	70	A
1411195	22	0 / -0,13	200	80	A
1411209	24	0 / -0,13	224	90	A
1411217	27	0 / -0,13	250	100	A
1411225	30	0 / -0,16	280	112	A
1411233	32	0 / -0,16	315	125	A
1411241	36	0 / -0,16	355	140	A

Article#	s	Tolerance	L1	L2	type
1411268	0,05"		42	13,5	B
1411276	1/16"		44	13,5	B
1411284	5/64"		47	15,5	B
1411292	3/32"		51	16,5	B
1411306	1/8"		57	19	B
1411314	5/32"		64	21,5	B
1411322	3/16"		70	24	B
1411330	7/32"		76	26	B
1411349	1/4"		83	29	B
1411357	5/16"		95	32	B
1411365	3/8"		108	35	B
1411373	1/2"		133	41	B
1411381	9/16"		146	45	B
1411403	5/8"		159	48	B
1411411	3/4"		184	54	B
1411438	1"		237	69	B