

Technical Datasheet



Halogen Free

FirestoP®

tasker® RG 58 PUR Coaxial 50Ω Mil. C 17 F Standard Cable



A	B	C	D
---	---	---	---

CATEGORY Coaxial cable 50 Ω (See Video Catalogue)

- A:** Black Polyurethane (**PUR**) sheath - Outer Cable Diam. Ø 5,00 (±0,20) mm.
- B:** Shielding O.F.C. tinned copper braid covering 98% .
- C:** Core Insulation with transparent compact PE – Diam. Ø 3,00 mm (±0,20) mm.
- D:** O.F.C. tinned copper stranded formation, 19x0,18 mm.
Nom. Cross section 1x0,48 mm² (50Ω).

MARKING CUSTOM

tasker® RG58 PUR 50 Ω Mil. C/17F OUTDOOR USE CABLE MADE IN ITALY
This product is also available in **L.S.Z.H., PE, PVC**, with or without **Steel Armor**.

Cable Properties

Conductor Resistance	40 Ω/Km ± 5%
Capacity Core/Shield	100 pF/mt
Velocity of Propagation	66%
Impedance	50 Ω ± 3%
Max Rated Voltage	2.000 V
Operative Temperature	-40/+80°C

Attenuation dB/100 mt.

50 MHz	9,7
100 MHz	13,9
200 MHz	20,4
400 MHz	30,0
800 MHz	45,1
1000 MHz	51,8

USE	X	Indoor	Interno Edificio
Impiego	X	Outdoor Limited	Esterno Limitato
		Outdoor Direct Burial	Esterno Interrato
			

INSTALLATION	X	Fixed	Fissa
Posa	X	Flexible Limited	Flessibilità limitata
	X	Dynamic (Drag Chain)	Mobile in Catena
		Dynamic (Torsion)	Mobile in Torsione

INFORMATION	X	RoHS2 Compliant
Informazioni	X	Ver. A / 12.01.16
		