



230 Vac

 8 Output Schuko Italy
TO PROTECT ALL
YOUR DEVICES

- 1 On/Off switch 2 Power cable 3 Input thermal protection 4 Output sockets with child protection and blackout protection 5 Filtered output socket with child protection 6 5Vdc 2.1A USB Charger 7 USB Port 8 RJ11/45 Port

Main Specifications

- Personal Computer, Modem/Router, Cash Register, Pos
- Automatic Voltage Regulation circuit (AVR)
- USB Charger (5V 2.1A) port
- Easy replacement batteries
- Rear slots for wall mounting
- Output sockets with child protection for blackout protection
- Output sockets with child protection for overvoltage protection
- USB port
- UPS Management Software TecnoManager compatible with Windows, Mac OS X, Unix, Linux, etc.



Specifications

UPS Model	ERA PLUS STRIP 1.000		ERA PLUS STRIP 1.000 UK	
Code	FGCERAPLS1002SCH		FGCERAPLS1002SCH	
Nominal power	1,000 VA			
Active power	700 W			
Power factor	0,7			
Technology	Line Interactive with stabilizer			
Cooling	Natural			
Audible noise	< 40 dBA to 1 m			
Input connection	Fixed cable with Schuko plug		Fixed cable with UK plug	
Outlets	4 UPS outputs Schuko/Italian + 4 only filtered outputs Schuko/Italian		4 UPS outputs UK + 4 only filtered outputs UK	
Dimension (UPS) WxHxD	20x10x34,5 cm			
Dimension (with packing) WxHxD	26,9x14,6x42,5 cm			
Weight	4,4 Kg			
Input				
Number of phases	1Ph+N			
Nominal voltage	Single-phase 230Vac			
Input voltage range	+20%/-25%			
Nominal frequency	50/60 Hz (automatic selection)			
Input frequency range	+/-5%			
Output				
Number of phases	1Ph+N			
Nominal voltage	Single-phase 230Vac			
Voltage regulation (Line mode)	AVR (Automatic Voltage Regulation)			
Voltage regulation (Battery mode)	+/-5%			
Frequency	50/60 Hz (automatic selection)			
Inverter waveform	Modified sinewave			
Overload capability	< 130%			
Transfer time	2 ms (typical)			
Battery				
Type	Lead acid, sealed, maintenance free			
Backup time (typical)	10-40 min			
Environmental specification				
Working temperature	From 0 to 40 °C (retcomended from 20 to 25 °C)			
Humidity	< 95% without condensation			
Maximum altitude	3000 m			
IP protection	IP20			
Certifications	CE (Standards: Low Voltage Directive IEC EN 62040-1; EMC Directive IEC EN 62040-2; classification IEC EN 62040-3)			

© 2021 Tecnoware Power Systems. The technical data may change without prior notice.

Available on request with input/output nominal voltage 110Vac or 120Vac and with input plug and output sockets for specific country.